

Supplementary materials

Lithology	(a) Thermal parameters				(b) Petrophysical parameters								(c) Mechanical parameters					
					Compaction						Permeability		Elastic		Plastic			
	S.m.c	T.D	H.C.	R.P.	ρs	φr	φa	φb	σa	σb	E _{obs}	Sp.surface	K An.	E	v	Pt	M	
Sandstone	6.32	0.004	700	5e-7	2675	0.01	0.44	0	30	0	10000	4.e6	1	9200	0.24	0.25	1.2	
70%-30% sandstone-shale	4.56	0.0032	740	9.5e-7	2665	0.01	0.49	0	28	0	1000	1.7e6	1	7500				
50%-50% sandstone-shale	3.67	0.0027	765	1.3e-6	2660	0.01	0.54	0	13.6	0	100000	1.e7	0.5	5700				
30%-70% sandstone-shale	2.95	0.0023	790	1.5e-6	2650	0.01	0.54	0	20	0	10000	1.2e7	1	5250				
Shale	2.37	0.002	815	1.9e-6	2654	0.04	0.56	0	16	0	20000	N/A	0.2	4500				
Evaporites	4.76	0.001	550	9.e-8	2700	0.01	0.29	0	40	0	10000	5.e7	1	1300				
Limestone	3.57	0.003	795	6.2e-7	2710	0.04	0.56	0	20	0	50000	4.e7	0.1	9000				
Upper crust	3	0.001	1150	3.5e-6	N/A													
Lower crust	2	0.001	1030	7e-7	N/A													
Upper Mantle	3	0	1200	0	N/A													
Water	N/A		3620	N/A	Water Salinity (g/L): 126.004, Water compressibility (1/L): 4.5e-5								N/A					

Table 1: Thermal, petrophysical and mechanical parameters used in the simulation. (a) Thermal parameters. S.m.c: Surface matrix conductivity W/(m.°C)), T.D.: Temperature Dependendy (1/°C), H.C.: Heat Capacity (J/(kg.°C)), R.P.: Radiogenic Production (W/m³). (b) Petrophysical parameters. ρs: solid volumic mass (kg/m³), φr: residual porosity, φa: observed porosity a, φb: observed porosity b, σa: observed sigma a (MPa), σb: observed sigma b (MPa), E_{obs}: Observed elasticity, for the PSM simulation only (MPa), Sp. Surface : Specific surface of the Kozeni Carman porosity-permeability law (1/m), K An.: vertical anisotropy multiplier. (c) Mechanical parameters. E: Young Modulus (MPa), v: poisson ratio, Pt: tensile intercept of the yield surface with the hydrostatic axis (MPa), M: slope of the Critical State Line.