

$$\varOmega_i = \{\, j_1, j_2, j_3, j_4\,\}$$









Fig. 3 Idealized 2-Dimentional matrix-fracture exchange



Fig. 4 Dual-porosity and dual-fracture model



Geometric coefficient calculation around a matrix block

## Fig. 5 Conductive connection between two fractured media



Fig. 6 Shape factor for exchanges between the matrix and the two fractured media



Fig. 7 Simulation domain with the matrix block of 100x25 m



Fig. 8 Comparison of shape factors on a single matrix block

Producer			
Inie	ctor		

Fig. 9 Horizontal doublet with fine grid around the fractures for the reference solution simulation



Fig. 10 Produced water temperature



Fig. 11 Temperature map of the reference solution at 1000 days for the horizontal doublet



Fig. 12 Pressure map of the reference solution at 1000 days



Fig. 13 Temperature map in the fracture cells of the standard dual-porosity model at 1000 days

## producer







15a). X-fracture medium

15b). Y-fracture medium











16e). Temperature in Zone Z4

Fig. 16 Average temperature in the four zones in the matrix medium near the corner



Fig. 17 Produced water temperature simulated with 5x5 grid cells at 1000 days with the horizontal doublet



Fig. 18 Temperature map of the reference solution at 1000 days with the vertical doublet



Fig. 19 Temperature map of the standard dual-porosity simulation at 1000 days with the vertical doublet



Fig. 20 Temperature maps of the dual-fracture model at 1000 days for the vertical doubet



Fig. 21 Produced water temperature at the production well



22c). Temperature in Zone Z3

22d). Temperature in Zone Z4

Fig. 22 Average temperature in the four zones of the matrix medium near the corner with the vertical doublet